

URBAN DURASKIN SÆSONSEJL



SPECIFIKATIONER FOR VERSEIDAG DURASKIN

Duraskin er en høj kvalitet dug, beregnet til brug i membraner, sol-/vejrsejl, telte og haller.

Dugen leveres coatet i PVC / PTFE / PU

Duraskin der er fremstillet i Tyskland, giver langvarig beskyttelse mod udefra kommende miljøpåvirkninger, der påvirker både mennesker og varer.

Duraskin leveres individuelt og skræddersyet til specifikke kundekrav/ønsker, i alt fra telte til store baldakiner og Sol-/vejrsejl, og opfylder de højeste krav med hensyn til miljø, overfladeforsegling og rengøring.

Leveres i 10 standard farver.

Minimumskrav til fald er 14°.

For optimalt spænd og holdbarhed, udføres alle sider med bue/radius med indsyet stålwire.

	standard		easy		standard low-wick		premium no-wick		standard opaque		premium opaque	
	B 1005		B 1013		B 1015		B 1017		B 1515		B 1673	
Total weight	550 g/m ²		650 g/m ²		630 g/m ²		650 g/m ²		750 g/m ²		850 g/m ²	
Tensile strength	2,000/2,000 N/5 cm		2,400/2,300 N/5 cm		2,800/2,500 N/5 cm		2,800/2,500 N/5 cm		3,000/2,800 N/5 cm		3,200/3,000 N/5 cm	
Tear resistance	200/180 N		230/210 N		300/250 N		300/250 N		300/280 N		350/300 N	
Adhesion	100 N/5 cm		100 N/5 cm		100 N/5 cm		100 N/5 cm		100 N/5 cm		100 N/5 cm	
Width	250 cm	300 cm	250 cm	300 cm	250 cm	300 cm	250 cm	300 cm	250 cm	300 cm	250 cm	300 cm
Colour	☐ White	☐ White	☐ White	☐ White	☐ White	☐ White	☐ White	☐ White	☐ White	☐ White	☐ White	☐ White
							☐ 032				☐ Black/White	
							☐ 048					
							☐ 057					
							☐ 063					
							☐ 064					
							☐ 070					
							☐ 029					
							☐ 168					
							☐ 001					

Note: Subject to change regarding technical upgrades. Values indicated without tolerance levels are nominal values with a tolerance range of ±5%. All data presented here is given to the best of our current knowledge for guidance purposes and is not legally binding. Further international certifications available.

Strøvej 38
3320 Skævinge, Danmark
Telefon: +45 48 28 80 99
E-mail: info@urban-elements.dk

UE
URBAN ELEMENTS